

SOW 6160

The SOW 6160 is a passive 2-way wall-mount speaker featuring a 6-inch low-frequency driver and a 1-inch dome tweeter. It includes a dedicated pan-and-tilt wall-mounting bracket for flexible horizontal and vertical positioning.



- 2-way speaker with 6-inch LF driver and 1-inch HF driver
- Compact and sturdy enclosure
- Balanced frequency response for warmth, detail and clarity
- Direct 8-ohm and 100V/70V inputs with multiple power taps
- Weatherised IP65 construction for outdoor use

- Powder-coated aluminium grille
- Powder-coated aluminium mounting bracket
- Horizontal and vertical tilt adjustment
- Available in white and black

DESCRIPTION	Wall mount speaker
SYSTEM	Passive 2 way bass reflex
TRANSDUCER	HF 1 x 1" dome tweeter, LF 1 x 6" woofer
FREQUENCY RESPONSE	60Hz ~ 20kHz, ± 6dB
POWER HANDLING DIRECT MODE	80W
POWER TAPS	100V: 7.5W, 15W, 30W, 60W 70V: 3.75W, 7.5W, 15W, 30W
NOMINAL IMPEDANCE	8Ω
SENSITIVITY (1W 1M)	90dB (half space)

MAX SPL DIRECT MODE	109dB
INPUT	Push type terminal, colour coded
IP RATING	IP65
GRILLE	Aluminium mesh powder coated
ENCLOSURE	Polypropylene
COLOURS	Black/White
DIMENSIONS W x H x D	200mm x 303mm x 181mm
NET WEIGHT	2.8kg
MOUNTING OPTIONS	Pan and tilt wall-mounting bracket

Due to continuous improvements, all specifications are subject to change