

SOW 6150

The SOW 6150 is a passive 2-way wall-mount speaker featuring a 5-inch low-frequency driver and a 1-inch dome tweeter. It includes a dedicated pan-and-tilt wall-mounting bracket for flexible installation.



- 2-way speaker with 5-inch LF driver and 1-inch HF driver
- Compact and sturdy enclosure
- Balanced frequency response for warmth, detail and clarity
- Direct 8-ohm and 100V/70V inputs with multiple power taps
- Weatherised IP65 construction for outdoor use

- Powder-coated aluminium grille
- Powder-coated aluminium mounting bracket
- Horizontal and vertical tilt adjustment
- Available in white and black

DESCRIPTION	Wall mount speaker
SYSTEM	Passive 2 way bass reflex
TRANSDUCER	HF 1 x 1" dome tweeter, LF 1 x 5" woofer
FREQUENCY RESPONSE	80Hz ~ 20kHz, ± 6dB
POWER HANDLING DIRECT MODE	60W
POWER TAPS	100V: 3.75W, 7.5W, 15W, 30W 70V: 1.77W, 3.75W, 7.5W, 15W
NOMINAL IMPEDANCE	8Ω
SENSITIVITY (1W 1M)	88dB (half space)

MAX SPL DIRECT MODE	105dB
INPUT	Push type terminal, colour coded
IP RATING	IP65
GRILLE	Aluminium mesh powder coated
ENCLOSURE	Polypropylene
COLOURS	Black/White
DIMENSIONS W x H x D	176mm x 252mm x 148mm
NET WEIGHT	2.3kg
MOUNTING OPTIONS	Pan and tilt wall-mounting bracket

Due to continuous improvements, all specifications are subject to change