

SOW 6140

The SOW 6140 is a compact passive 2-way wall-mount speaker featuring a 4-inch low-frequency driver and a 1-inch dome tweeter. It includes a dedicated pan-and-tilt wall bracket for flexible positioning.



- 2-way speaker with 4-inch LF driver and 1-inch HF driver
- Compact and sturdy enclosure
- Balanced frequency response for warmth, detail and clarity
- Direct 8-ohm and 100V/70V inputs with multiple power taps
- Weatherised IP65 construction for outdoor use

- Powder-coated aluminium grille
- Powder-coated aluminium mounting bracket
- Horizontal and vertical tilt adjustment
- Available in white and black

DESCRIPTION	Wall mount speaker
SYSTEM	Passive 2 way bass reflex
TRANSDUCER	HF 1 x 1" dome tweeter, LF 1 x 4" woofer
FREQUENCY RESPONSE	90Hz ~ 20kHz, ± 6dB
POWER HANDLING DIRECT MODE	40W
POWER TAPS	100V: 2.5W, 5W, 10W, 20W 70V: 1.25W, 2.5W, 5W, 10W
NOMINAL IMPEDANCE	8Ω
SENSITIVITY (1W 1M)	86dB (half space)

MAX SPL DIRECT MODE	102dB
INPUT	Push type terminal, colour coded
IP RATING	IP65
GRILLE	Aluminium mesh powder coated
ENCLOSURE	Polypropylene
COLOURS	Black/White
DIMENSIONS W x H x D	136mm x 196mm x 131mm
NET WEIGHT	1.7kg
MOUNTING OPTIONS	Pan and tilt wall-mounting bracket

Due to continuous improvements, all specifications are subject to change