

SONODYNE®

SPS 1040



The SPS 1040 is a 2-way pendant loudspeaker featuring a coaxial 4-inch transducer.

- Smooth frequency response with uniform coverage
- 2-way design with 4-inch LF driver and dome tweeter
- Stylish and sturdy polypropylene enclosure
- Variable wattage taps for 100V and 70V operation
- Suspension kit with 1-metre wire rope, snap hooks and mounting eye-bolt
- Suitable for indoor and outdoor use
- Can also be wall-mounted or floor-mounted
- Available in black and white

DESCRIPTION	Pendant speaker
SYSTEM	Passive 2 way bass reflex
ENCLOSURE	Polypropylene
TRANSDUCER	1 x 4" woofer, 1 x 3/4" dome tweeter
FREQUENCY RESPONSE	80Hz ~ 20kHz, $\pm$ 6dB
POWER HANDLING	40W (direct mode)
POWER TAPS	70V: 1.25W, 2.5W, 5W, 10W 100V: 2.5W, 5W, 10W, 20W
SENSITIVITY (1W 1M)	83dB
MAX SPL DIRECT MODE	100dB

INPUT	Pluggable terminal block
NOMINAL IMPEDANCE	8 Ω
IP RATING	IP65
GRILLE	Aluminium mesh powder coated
COLOURS	Black/White
DIMENSIONS Dia x Height	155mm x 215mm
PACKING	Pair
NET WEIGHT	1.9kg
BRACKET	Wall mount, Floor mount (sold separately)
MOUNTING OPTIONS	Wire rope including eyebolts

Due to continuous improvements, all specifications are subject to change