

SONODYNE®

SPS 1050



The SPS 1050 is a 2-way pendant loudspeaker featuring a coaxial 5-inch transducer.

- Smooth frequency response with uniform coverage
- 2-way design with 5-inch LF driver and dome tweeter
- Stylish and sturdy polypropylene enclosure
- Variable wattage taps for 100V and 70V operation
- Suspension kit with 1-metre wire rope, snap hooks and mounting eye-bolt
- Suitable for indoor and outdoor use
- Can also be wall-mounted or floor-mounted
- Available in black and white

DESCRIPTION	Pendant speaker
SYSTEM	Passive 2 way bass reflex
ENCLOSURE	Polypropylene
TRANSDUCER	1 x 5" woofer, 1 x 1" dome tweeter
FREQUENCY RESPONSE	65Hz ~ 20kHz, ± 6 dB
POWER HANDLING	50W (direct mode)
POWER TAPS	70V: 1.77W, 3.75W, 7.5W, 15W 100V: 3.75W, 7.5W, 15W, 30W
SENSITIVITY (1W 1M)	85dB
MAX SPL DIRECT MODE	103dB

INPUT	Pluggable terminal block
NOMINAL IMPEDANCE	8 Ω
IP RATING	IP65
GRILLE	Aluminium mesh powder coated
COLOURS	Black/White
DIMENSIONS Dia x Height	190mm x 250mm
PACKING	Pair
NET WEIGHT	2.55kg
BRACKET	Wall mount, Floor mount (sold separately)
MOUNTING OPTIONS	Wire rope including eyebolts

Due to continuous improvements, all specifications are subject to change