

SONODYNE®

SPS 1060



The SPS 1060 is a 2-way pendant loudspeaker featuring a coaxial 6.5-inch transducer.

- Smooth frequency response with uniform coverage
- 2-way design with 6.5-inch LF driver and dome tweeter
- Stylish and sturdy polypropylene enclosure
- Variable wattage taps for 100V and 70V operation
- Suspension kit with 1-metre wire rope, snap hooks and mounting eye-bolt
- Suitable for indoor and outdoor use
- Can also be wall-mounted or floor-mounted
- Available in black and white

DESCRIPTION	Pendant speaker
SYSTEM	Passive 2 way bass reflex
ENCLOSURE	Polypropylene
TRANSDUCER	1 x 6.5" woofer, 1 x 1" dome tweeter
FREQUENCY RESPONSE	50Hz ~ 20kHz, ± 6 dB
POWER HANDLING	60W (direct mode)
POWER TAPS	70V: 2.5W, 5W, 10W, 20W 100V: 5W, 10W, 20W, 40W
SENSITIVITY (1W 1M)	88dB
MAX SPL DIRECT MODE	106dB

INPUT	Pluggable terminal block
NOMINAL IMPEDANCE	8 Ω
IP RATING	IP65
GRILLE	Aluminium mesh powder coated
COLOURS	Black/White
DIMENSIONS Dia x Height	230mm x 300mm
PACKING	Pair
NET WEIGHT	3.45kg
BRACKET	Wall mount, Floor mount (sold separately)
MOUNTING OPTIONS	Wire rope including eyebolts

Due to continuous improvements, all specifications are subject to change