SONODYNE®

SSW 2010

The SSW 2010 is a high performance on wall subwoofer with operations in both mono and stereo mode. With inbuilt HPF, it can be operated in 100 volt or 4 Ohm mode.

- Wall mounted subwoofer
- In-built crossover for high pass to satellite speakers
- Both stereo and mono modes
- Both direct and LMT modes
- Smooth, articulated response
- Transducer with dual voice coil

DESCRIPTION	Side firing subwoofer, vented
ENCLOSURE	MDF
TRANSDUCER	1 x 6" dual voice-coil subwoofer
FREQUENCY RANGE	45Hz ~ 200Hz
FREQUENCY RESPONSE	50Hz ~ 200Hz
SENSITIVITY (1W 1M)	88dB (half space)
SPL	105dB @ 60W
AMPLIFIER POWER	100W + 100W direct input

POWER TAPS	70V: 7.5W, 15W, 30W 100V: 15W, 30W, 60W
IMPEDANCE	70V: 653, 327, 163Ω 100V: 666, 333, 167Ω
COLOURS	Black/White
DIMENSIONS WxHxD	450mm x 350mm x 180mm
NET WEIGHT	12.2kg
MOUNTING OPTIONS	Wall-mounting brackets

Due to continuous improvements, all specifications are subject to change

www.sonodyne.com I response@sonodyne.com I 1-800-313 3380

MADE IN INDIA
since 1970