SONODYNE®



# SSW 1030



The SSW 1030 is a high power subwoofer with operations in both mono and stereo mode. With inbuilt HPF, it can be operated in 8 Ohms and 4 Ohms mode

- Wall mounted subwoofer
- In-built crossover for high pass to satellite speakers
- Both stereo and mono modes
- High SPL and power handling
- Transducer with dual voice coil
- Smooth, articulated response

| | |
|---|---|
| DESCRIPTION | On Wall/ On Floor Subwoofer |
| ENCLOSURE | MDF |
| TRANSDUCER | 1 x 10" dual voice-coil subwoofer |
| FREQUENCY RANGE | 40Hz ~ 180Hz |
| FREQUENCY RESPONSE | 45Hz ~ 180Hz |
| SENSITIVITY (1W 1M) | 95dB (half space) |
| SPL | 119dB @ 300W |

| | |
|---|---|
| IMPEDANCE | 4Ω + 4Ω (stereo), 8Ω (mono) direct mode |
| IMPEDANCE 70V | 490, 245, 122Ω |
| AMPLIFIER POWER | 300W + 300W direct input |
| COLOURS | Black/White |
| DIMENSIONS WxHxD | 580mm x 325mm x 335mm |
| NET WEIGHT | 16.5kg |
| MOUNTING OPTIONS | Wall-mounting brackets (included) |

*Due to continuous improvements, all specifications are subject to change*

www.sonodyne.com I response@sonodyne.com I 1-800-313 3380

**MADE IN INDIA**
since 1970